AWM3529/3135/3530

产品结构

- 单根或多股镀锡铜线绞合软导体，镀锡铜线性能参考 GB/T4910-2022 标准；导体的结构参考 UL758&UL1581 或客户的要求
- 硅橡胶绝缘，绝缘材料性能参考 UL758&UL1581；成品电线电缆的外径检验方法参考 UL758&UL1581；成品电线电缆电性能检验方法参考 UL758&UL1581

技术数据

- 温度范围：-60~+150/+200°C ・ 额定电压：U0/U 600V ・ 测试电压：2000V
- 绝缘电阻：20°C时应不小于 100MΩ・km

产品特性

- 具有优良的环保性，无味无毒，极好的抗血栓性、生物惰性；优良的电绝缘性能；具有中等的耐油、耐溶剂性能；在高温环境下电气性能稳定，抗老化性能好，使用寿命长。可在长期潮湿环境中使用，电性能及防水、防霉性能优越；硅橡胶非常柔软，具有良好的弹性，弯曲且柔软，便于安装
- 可选 - 燃烧气体的腐蚀性（无卤素）符合 DIN VDE0482 第 267 部分，DINEN50267-2-2,IEC60754-2（等效 DIN VDE0472 第 813 部分）；火灾中的行为无火焰传播应符合 DIN VDE0482-332-1-2/DIN EN60332-1-2/IEC60332-1（等效 DINVDE0472part804 测试方法 B）
- 不含有害物质，符合 ROHS 标准

应用范围

- 用于钢铁生产工业、航空工业以及造船、水泥、玻璃和陶瓷厂。由于这种单芯线不含卤素，特别适用于发电站
- 广泛应用于照明灯具、家用电器、电热电器、仪器仪表、电机引接线及电子、灯具、染具等高温线环境

Product Structures

- Single or multi-stranded tinned copper wire flexible conductor. Tinned copper wire performance: Compliant with GB/T4910-2022; Conductor structure: Compliant with UL758&UL1581 or customer requirements.
- Insulation: Silicone rubber insulation. Insulation material performance: Compliant with UL758&UL1581; Outer diameter testing: UL758&UL1581, Electrical performance testing: UL758&UL1581

Technical data

- Temperature range: -60~+150/+200°C
- Rated voltage: U0/U 600V
- Test voltage: 2000V
- Insulation resistance: ⩾ 100MΩ・km at 20°C

Product Features

- Eco-friendly & biocompatible: Odorless, non-toxic, anti-thrombogenic, biologically inert
- Superior electrical insulation: Stable performance at high temperatures
- Durability: Excellent aging resistance, extended service life
- Environmental resistance:
  - - Moderate oil/solvent resistance
  - - Waterproof, anti-mold properties for humid environments
- Flexibility: Highly soft and elastic for easy installation
- Optional Halogen-free Certification:
  - - Corrosive gas emission: Compliant with DIN VDE 0482-267 / EN 50267-2-2 / IEC 60754-2
  - - Flame propagation resistance: Compliant with DIN VDE 0482-332-1-2 / EN 60332-1-2 / IEC 60332-1
- Eco-friendly: ROHS compliant

Applications

- Heavy Industries:
  - - Steel production, aviation, shipbuilding
  - - Cement/glass/ceramic plants
  - - Halogen-free critical areas: Power stations
- High-temperature environments:
  - - Lighting fixtures, household appliances
  - - Electric heating equipment, instrumentation
  - - Motor lead wires, electronics
  - - Dyeing equipment and industrial heating systems

技术参数 Technical parameters

线规 Guage (AWG)	导体结构 根数 / 线径 Conductor construction: Number/ size (mm)	绝缘厚度 Insulation thickness (mm)	平均外径 Average outer diameter (mm)	20°C时导体直流电阻 Max(Ω/km) The maximum resistance value of the conductor at 20°C (Ω/km)	包装长度 The length of package (m)
12	19×0.49	0.76	4.30	5.64	305
14	19×0.37	0.76	3.50	8.96	305
16	7×0.50	0.76	3.10	14.6	305
17	7×0.45	0.76	3.00	18.3	305
18	7×0.40	0.76	2.80	23.2	305
20	7×0.32	0.76	2.60	36.7	305
22	7×0.26	0.76	2.40	59.4	610
24	7×0.20	0.76	2.20	94.2	610
26	7×0.16	0.76	2.10	150	610